

# BASKET FAN RE-CIRCULATION

## HIGHT OUTPUT PERFORMANCE, LOW COST!

Our Deluxe Basket Fan Series combines high output performance, low cost and maintenance and energy efficiency to give you one of our best valued fan series. It gives a high velocity air pattern with quiet operation.

## WHEN APPLIED PROPERLY SECCO CIRCULATION FANS CAN BE USED IN THE FOLLOWING APPLICATIONS:

- Air de-stratification reduces heating and cooling bills
- Air exchange when placed in a wall opening or in open sidewall buildings
- Consistent air temperature throughout a room, building or barn
- Heat stress relief indoors and outdoors for young and old
- Surface drying (including animal bedding)
- People and animal cooling
- Machine/compressor cooling
- High velocity air cooling
- Insect control



## FEATURES

- Comes with hot dip galvanized standard mounting bracket
- OSHA approved guard for installations below and above 7' (2.13 m)
- Corrosion resistant powder coated guards
- Variable speed motors on select models
- Maintenance free, direct drive high efficiency motors has completely sealed ball bearings, UL, ULC and CE certification
- 1 year warranty on all parts



SIZE	DRIVE	HP (KW)	VOLT	PH	AMP	RPM	HZ	CFM (M <sup>3</sup> /H) 0" SP	CFM/WATT (M <sup>3</sup> /H/WATT) 0" SP	FPM (KM/H) @ 50' (15 M)	FPM (KM/H) @ 100' (30 M)	BLADE	CORD *	WEIGHT	SPEED
12" (30 CM)	DD	1/10 (0.07 KW)	115/230	1	1.42/0.77	1 725	50/60	1 600 (27 185 M <sup>3</sup> /H)	16 (27 M <sup>3</sup> /H)	200 (3.7 KM)	50 (0.9 KM)	3-ALUM.	9' (2.74 M)	21.75 (9.86 KG)	VARIABLE
20" (51 CM)	DD	1/3 (0.25 KW)	115/230	1	4.3/2.16	1 725	50/60	6 400 (10 874 M <sup>3</sup> /H)	17 (29 M <sup>3</sup> /H)	450 (8.2 KM)	150 (2.7 KM)	3-ALUM.	9' (2.74 M)	36.5 (16.55 KG)	VARIABLE
24" (61 CM)	DD	1/2 (0.37 KW)	115/230	1	5.2/2.8	1 725	50/60	8 800 (1 495 M <sup>3</sup> /H)	18 (31 M <sup>3</sup> /H)	550 (10.1 KM)	200 (3.7 KM)	3-ALUM.	9' (2.74 M)	46.5 (21.09 KG)	VARIABLE
36" (91 CM)	DD	1/2 (0.37 KW)	115/230	1	6.1/3.09	825	50/60	14 000 (23 787 M <sup>3</sup> /H)	26 (37 M <sup>3</sup> /H)	700 (12.8 KM)	350 (6.4 KM)	3-GALV.	N/A	65 (29.48 KG)	SINGLE

\* The supplied powercord is only useful on 115 V. for 230 V. you must remove the powercord and re-do the electrical connections to the motor.

For more information:

# seccoventilation.com

Distributed by:

Division of Secco International Inc.  
4040, blvd Casavant West  
St-Hyacinthe (Quebec) Canada • J2S 8E3  
Phone: 450 771.0777 • 877 711.0777  
Fax: 450 771.5779  
secco@ventilationsecco.com

